

## METAL + ENAMEL | Cleaning and Finish Care

Please read over the "Cleaning and Finish Care" instructions before taking care of your range hood. Call us at 970.848.8851 with any questions. We're here to help!

**PRIOR TO INSTALLATION** | Be sure to wear the supplied latex gloves throughout install to avoid smudges and oils from the skin. Long sleeves are recommended.

Avoid wearing clothes with metal pieces. Buckles, zippers, buttons, and rings can scratch and ruin the metal and the finish.

Clean and dry both sides of the wall paneling to clear off any dust. This is VERY important for a proper and safe install!

## **IMPORTANT NOTE!**

Allow up to 90 days before cleaning your hood. Also, avoid contact with citrus juice, vinegar, ammonia, other acids, or cleaners. If contact occurs, rinse immediately.

**DO NOT USE** | Cleaning tools like abrasive cloths, scrubbing brushes, Brillo pads, etc. They can scratch the surface of the metal or enamel.

Do not use any cleaning products beyond what is recommended in this "Cleaning and Finish Care" instructions sheet. DO NOT use any harsh chemicals, homemade cleaners, etc.

Do not stick anything on the surface including tape or sticky notes! This can lift the clear coat and ruin the patina underneath.

If something happens, call us. DO NOT attempt to refinish or fix paneling without Raw Urth.

WHAT TO USE | We highly recommend using the product, Sprayway, Ammonia Free, Foaming Action Class Cleaner for everyday cleaning. You can purchase it on Amazon or at a general store. No other glass cleaners can be used.

Sprayway.

World's Best ... §

It's streakless!

Use only a soft, clean microfiber cloth, rubbing in a circular motion when cleaning your range hood. Dry immediately.

If you have grease build up, use a mild dish soap like Dawn Dish Soap with a soft, microfiber cloth.

We provide clear coat touch up kits for light scratches in the clear coat. Just call us and we'll send your way.

